# 108.08 AC

Quality PTFE / glass fabrics coated on one side with acrylic pressure sensitive.

Smooth blue PE liner is applied to the adhesive surface for ease application.

Product	Product category	Coating
PTFE GLASS FABRIC SELF ADHESIVE	ACRYLIC SERIES	ACRYLIC PSA

Properties	Metric		Imperial	
Standard width(s) *Please ask for other widths*	1000	mm	39.5	inches
Nominal backing thickness *(PTFE glass)*	0,08	mm	0.0031	inches
Backing weight *(PTFE glass)*	155	gr/m²	4.57	oz/sq yd
Nominal total thickness *(PTFE glass and acrylic PSA)*	0,13	mm	0.0051	inches
Adhesion	17,5	N/5 cm	32	oz/inches
Temperature resistance	-40 to +170	°C	-104 to +338	°F

PRECAUTION REMINDERS
Please kindly pay attention our precaution reminders before applying Fiberflon pressure-sensitive adhesives tapes. Prior to application, surface should be inspected carefully. Application surface should be clean, oil-free, without moisture and dirt. If the surface is extremely uneven or distorted, the tape may not adhere well. When applying, Fiberflon PSA tapes may require some pressure through roller, hand or press. Once applied, please allow sufficient time for full adhesive strength.

GENERAL STORAGE CONDITIONS
Best stored between 10°C-27°C / 50°F- 80°F, 25-50% relative humidity, out of direct sunlight.

The product does not contain banned substances as described in RoHS directive and will not affect RoHS compliance.

This product has been manufactured in a facility certified by ISO 9001 Quality Management System.

www.fiberflon.com