

628.25 BLUE



Product	Product category	Coating
PTFE GLASS FABRIC	SPECIALTY SERIES	PTFE

Properties	Metric		Imperial	
Standard width(s) <i>Please ask for other widths</i>	1250, 1500	mm	49.3, 59.1	inches
Nominal thickness	0,24	mm	0.0094	inches
Weight	490	gr/m ²	14.45	oz/sq yd
PTFE content	57	%	57	%
Tensile strength	2300	N/5 cm	263	Ibs/inches
Temperature resistance	-150 to +260	°C	-238 to +500	°F

628.25 BLUE is a smooth PTFE-coated glass fabric with superior release properties and excellent thermal transfer ensures most efficient production. Increased puncture resistance, resistance to abrasion and oil penetration maximizes belt lifetime.

628.25 BLUE is typically used as conveyor belt in tortilla and various food cooking processes, industrial belting and release sheets in plastic, packaging and polymer processing.

The product can be used in direct contact with food.

The product does not contain banned substances as described in RoHS directive and will not affect RoHS compliance.



This product has been manufactured in a facility certified by ISO 9001 Quality Management System.

Note: Nominal thickness, weight and tensile strength values are typical and are not intended as a specification minimum.

Nominal thickness tolerance: ±0,02 mm - Weight tolerance g/m² = ±%5 - Tensile strength tolerance -%10

All technical data are based on average values. These values are not intended for use in preparing specifications. Technical information contained herein are based on test results FIBERFLON believes to be reliable, but they are not to be construed in any manner as warranties expressed.

All data is subject to change without notice.