

# SIL 056 R



| Product                             | Product category   | Coating         |
|-------------------------------------|--------------------|-----------------|
| SILICONE RUBBER COATED GLASS FABRIC | SILICONE BOTH SIDE | SILICONE RUBBER |

| Properties  | Metric      |                   | Imperial     |          |
|---|-------------|-------------------|--------------|----------|
| Standard width(s)<br><i>Please ask for other widths</i> | 1000        | mm                | 39.5         | inches   |
| Nominal thickness                                       | 0,56        | mm                | 0.0220       | inches   |
| Weight  | 700         | gr/m <sup>2</sup> | 20.65        | oz/sq yd |
| Temperature resistance                                  | -70 to +230 | °C                | -158 to +446 | °F       |

Glass fabrics coated on both side with silicone rubber.

- Hi-temperature resistant
- Excellent release properties
- Superior abrasion resistance
- Good chemical resistance
- Superior dielectric properties

Fiberflon silicone coated fabrics can be used a wide range of industrial applications, such as; Shrink tunnels, foam manufacturing, electrical insulation tapes, conveyor belts, fabric expansion joints, safety curtains, release and separator sheets, gasketing.

The product does not contain banned substances as described in RoHS directive and will not affect RoHS compliance.



This product has been manufactured in a facility certified by ISO 9001 Quality Management System.

Note: Nominal thickness and weight values are typical and are not intended as a specification minimum.

Nominal thickness tolerance: ±0,03 mm - Weight tolerance g/m<sup>2</sup> = ±%5

All technical data are based on average values. These values are not intended for use in preparing specifications. Technical information contained herein are based on test results FIBERFLON believes to be reliable, but they are not to be construed in any manner as warranties expressed.

All data is subject to change without notice.